



ONE BRAND ONE SOURCE ONE SYSTEM

LEVIERS



| Référence | Désignation | Longueur en mm | Particularité | |
|-----------|-------------|----------------|--|-----|
| 0545240 | Moto | 380 mm | | J |
| 0505230 | Fusil | 380 mm | | A |
| 0515240 | Face | 530 mm | | C/D |
| 0525240 | Force | 750 mm | | C/D |
| 0575240 | Fifre | 420 mm | Pneus tubeless ou tube/jante plate | C |
| 0555240 | Flacre | 460 mm | | C |
| 0505240 | Haite | 800 mm | Pneus tubeless/jante base creuse 15° | C |
| 0585240 | Hyoca | 935 mm | Pneus Double X forestier/jante base creuse 15° | D/E |
| 0595240 | Hyude | 990 mm | Pneus Double X forestier | D/E |
| 0565240 | Sayam | 950 mm | | E |

Le conseil TIP TOP


Il est important de préserver le talon du pneu lors du démontage et du montage. Utiliser le levier adapté au type et à la dimension du pneu.



Moto – Réf. : 0545240



Fusil – Réf. : 0505230



Face – Réf. : 0515240



Force – Réf. : 0525240



Hyude – Réf. : 0595240



Fifre – Réf. : 0575240



Flacre – Réf. : 0555240



Haite – Réf. : 0505240



Hyoca – Réf. : 0585240



Sayam – Réf. : 0565240